

P-BE stainless steel housing for aeration of storage tanks

P-BE stainless steel housing

Ultrafilter P-BE

- P-BE Iter are used to ensure 100 % sterility in the storage of pharmaceutical products, chemicals, food or of fermenerts.
- The two-part housing is user-frienldy designed and has a splash protection to prevent liquids coming in contact with the filter media.

Features and benefits

- 12 different sizes for operating volumes from 3 to 1980 Nm³/h related to 1 bar.
- Complies to the requirements of the European directive 97/23/EG for pressure vessels.
- Different element sizes can be used due to the modular design. Apart from sterile filters, polypropylene or Teflon* membrane filters can be used.

Surface finish
Polished on the inside and on the outside

Applications

- Breweries, Dairies
- Chemical industry, Pharmaceutical industry
- Cosmetics Industry
- Water treatment systems
- food and beverages

Connection types				
Milkpipe DIN 11851	standard for 0006 – 0192			
DIN or ANSI flange	standard, starting from 0432 housing			
Clamp connection or other connections and bigger housings on request				

Maximum operating temperature:	
200°C	

Maximum operating pressure:				
housing size 0006 – 0192	16 bar			
housing size 0432 - 1920	10 bar			

Materials	
Filter housing	stainless steel 1.4301 (304), optional 1.4571 (316L)

volume flow housing size in m³/h at		connection		lement	dimensions in mm		weight in kg	
	Δp 20 mbar	Δp 40 mbar		size	qty.	height	Ø	
0006	4,5	9	DN 32	03/10	1	110	85	1,5
0027	12	24	DN 40	05/25	1	168	104	2,2
0032	17	35	DN 50	05/30	1	186	114	2,4
0072	35	70	DN 50	10/30	1	312	114	3,3
0144	70	140	DN 80	20/30	1	550	154	9,2
0192	105	210	DN 80	30/30	1	805	154	11,5
0432	210	420	DN 100	20/30	3	670	219	43,0
0576	315	630	DN 100	30/30	3	925	219	44,0
0768	420	840	DN 150	30/30	4	950	273	70,0
1152	630	1260	DN 150	30/30	6	950	324	80,0
1536	840	1680	DN 200	30/30	8	960	406	135,0
1920	1050	2010	DN 200	30/30	10	960	406	135,0



e-Mail: info@ultra-filter.de • www.ultra-filter.de